

CONSTRUCTION DATA SHEET

GENERAL SPECIFICATIONS	
Interface	LC/UPC
Body Style	Simplex
Connector Color	Violet
Jacket Color	Violet
Standard	IEC61754-20-2002
Length	1.5 m
Regulatory Compliance/ Certifications	ROHS 2.0 Compliant
OPTICAL SPECIFICATIONS	
Fibre Mode	Multimode
Fibre Type	OM4
Insertion Loss, maximum	0.20 dB
Return Loss, minimum	25 dB
MECHANICAL SPECIFICATIONS	
Bending Radius	20D (Dynamic), 10D (Static)
Durability	>500 times
ENVIRONMENTAL SPECIFICATIONS	
Operating Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
PACKAGING	
	10pcs/Pack

ORDERING INFORMATION AS PER FOLLOWS

PART NO	PRODUCT NAME	COLOR	LENGTH	PACKAGING
KB-FPM4-LC	OM4 Fibre Optic Pigtail, LC/UPC	Violet	1.5m	10pcs/Pack

OTHER PRODUCTS INCLUDE

SC/UPC SINGLE MODE FIBRE OPTIC PIGTAIL	LC/APC SINGLE MODE FIBRE OPTIC PIGTAIL	LC/UPC SINGLE MODE FIBRE OPTIC PIGTAIL	SC/APC SINGLE MODE FIBRE OPTIC PIGTAIL
OM3 FIBRE OPTIC PIGTAIL, LC/UPC	OM3 FIBRE OPTIC PIGTAIL, SC/UPC	OM4 FIBRE OPTIC PIGTAIL, SC/UPC	